

Benefits

1. developed for year round use
2. especially developed for racing and ideally suited for motorcycles
3. optimum lubrication even under extreme conditions

Product Description

BIZOL Technology 10W-60 is a fully synthetic, high-performance engine oil. The synthetic components give it an extremely high quality level that is particularly useful for engines that are exposed to high thermal stress.

Base Oil

Fully Synthetic

Specifications/Approvals & Recommendations

API SL/CF | JASO MA-2

Available Packages

1 L

Art. 89310

Technical Data

Name	Value	Method
Viscosity class SAE	10W-60	SAE J 300
Viscosity at 40 °C	164,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	23,0 mm ² /s	ASTM D 7042
Viscosity index	170	ASTM D 2270
Density at 15 °C	850 kg/m ³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Flash Point (Cleveland)	220 °C	ISO 2592
ASTM colour number	L5,0	ASTM D1500
Sulfate ashes	0,90 %	DIN 51 575



Technical Data

Name	Value	Method
Total base number (TBN)	8,2 mg KOH/g	ASTM D 2896

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.