

Benefits

1. excellent safety against wear, corrosion and foaming
2. provides superior transmission life
3. suitable for DEXRON VI requirements

Product Description

BIZOL Protect ATF D-VI belongs to the latest generation of automatic transmission fluids based on HC-synthesis combined with a modern, high-performance additive package. It meets the requirements of many car and automatic gear box manufacturers all over the world. BIZOL Protect ATF DVI is designed for the use in automatic transmissions as well as hydraulic and power steering systems in both passenger cars and commercial vehicles.

Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

GM Dexron VI*/Dexron III G/Dexron III H/Dexron II D/Dexron TASA |

Ford Mercon V* | JASO 1 A

MB 236.3/236.5/236.6/236.7/236.8/236.9/236.10/236.11/236.91 |

BMW P/N 81 22 9 400 272/P/N 81 22 9 400 275/P/N 81 22 9 407 858/P/N 81 22 9 407 859/P/N 83 22 0 024 359/P/N 83 22 0 026 92

| VW G 052 025/G 052 162/G 052 990/G 055 025/G US 000 162 |

Mazda ATF M III/ATF M-V/Type T-IV/ATF F1 |

Mitsubishi ATF-J2/SP-II/SP-III/P/N MS 991156 |

Nissan N 402/Matic D/Matic J/Matic K | Chrysler ATF+3/ATF+4 |

Honda ATF-Z1 | Hyundai SP-II/SP-III/NWS-9638/SPH-IV |

Suzuki 3314/3317 | Kia SP II/SP-III | Subaru ATF HP/P/N K 0140 Y 0700 |

Volvo 97341/P/N 1161540/P/N 1161640/VCE 1273.41 |

Porsche P/N 000 043 204 41/P/N 000 043 205 28/P/N 999 917 547 00 |

Renault Matic D2 | PSA Peugeot Citroen P/N Z 000169756 |

Aisin Warner AW-1/JWS 3309/JWS 3324 | Saab 93 165 147 |

Isuzu ATF III/P/N 0820-9001 | SSANG YONG DSIH 5M-66 |

Voith 55.6335.XX (G607) | Bentley JNV 862 564 D |

Jaguar JLM 20238/JLM 21044/K17/WSS-M2C922-A1 |

Allison C4/TES 295/TES 389 | ZF TE-ML 05L/09/11A/11B

*

Available Packages

1 L Art. 27310	5 L Art. 27311	20 L Art. 27312
-------------------	-------------------	--------------------

Technical Data

Name	Value	Method
Viscosity at 40 °C	34,4 mm ² /s	ASTM D 7042
Viscosity at 100 °C	6,7 mm ² /s	ASTM D 7042
Viscosity index	155	ASTM D 2270
Density at 15 °C	860 kg/m ³	DIN EN ISO 12 185
Pour Point	-48 °C	ISO 3016
ASTM colour number	> L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	220 °C	ISO 2592

Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.