

## Benefits

1. suitable for mechanically and electronically controlled automatic transmissions
2. outstanding performance at both high and low temperature extremes
3. improved power transmission efficiency and smooth transmission operation

## Product Description

**BIZOL Protect ATF LV** is a modern high-performance ATF for new generation automatic transmissions with low viscosity requirements. The combination of high-quality base oils and advanced additive technology ensures an excellent ageing and oxidation stability as well as superior wear protection. It allows for smooth shifting at extremely low ambient temperatures and allows for longer oil change intervals. **BIZOL Protect ATF LV** contains seal conditioner that maintain seals from ageing for optimal transmissions performance.

## Base Oil

HC-Synthetic

## Specifications/Approvals & Recommendations

GM Dexron VI | Ford Mercon LV | JASO 1 A/1-A-LV  
MB 236.12/236.14/236.15/236.41 |  
VW G 052 162/G 055 005/G 055 162/G 055 540/G 060 162 |  
BMW P/N 83 22 0 142 516/P/N 83 22 2 152 426/P/N 83 22 2 289 720/P/N 83 222 355 599/M-1375.4  
| ZF Lifeguardfluid 6/Lifeguardfluid 8 | Toyota WS |  
Nissan Matic S/Matic W | Mitsubishi SP-IV/Dia Queen ATF-PA/ATF-J3 |  
Hyundai SP-IV/SPH-IV/FF-SP-IV M/NWS-9638 | Kia SP-IV/SPH-IV |  
Honda DW-1/3.1 | Mazda ATF FZ/ATF 3.1 |  
Aisin Warner GM-AW-1/JWS 3324 | Saab 93 165 147 AW1 |  
Bentley JNV 862 564 D | Jaguar 02JDE26444 | Land Rover LR023288 |  
Volvo 31246675/31256774 | Fiat 9.55550-AV5

## Available Packages

1 L	5 L	20 L
Art. 28750	Art. 28751	Art. 28752

## Technical Data



Name	Value	Method
Viscosity at 40 °C	27,3 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	5,7 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	156	ASTM D 2270
Density at 15 °C	840 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	<-42 °C	ISO 3016
ASTM colour number	> L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	>180 °C	ISO 2592

## Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.