

## Benefits

1. best protection against soot thickening
2. prevents deposits on the pistons-rings
3. long lifetime of the engine oil

## Product Description

BIZOL Allround 5W-40 is a modern high-performance engine oil that grants optimal protection against wear, premature aging and sludging. The selection of friction modifying and corrosion inhibiting additives as well as the use of high-quality base oils provide for excellent lubricity especially under extreme conditions. Thus BIZOL Allround 5W-40 ensures permanent protection from deposits on parts which are prone to wear. This engine oil allows for extended maintenance intervals.



## Base Oil

HC-Synthetic

## Specifications/Approvals & Recommendations

ACEA A3/B4 | API SN/CF  
MB 229.3 | BMW LL 01 | VW 502 00/505 00 | GM LL A-025/LL B-025 |  
Porsche A40 | Renault RN 0700/RN 0710 | Fiat 9.55535 N2 |  
Peugeot B71 2296

## Available Packages

1 L	4 L	5 L	5 L
Art. 85220	Art. 85226	Art. 35221	Art. 85221
20 L	60 L	200 L	
Art. 85222	Art. 85223	Art. 85224	

## Technical Data

Name	Value	Method
Viscosity class SAE	5W-40	SAE J 300
Viscosity at 40 °C	87,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	14,5 mm <sup>2</sup> /s	ASTM D 7042

## Technical Data

Name	Value	Method
Viscosity index	174	ASTM D 2270
Density at 15 °C	860 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
ASTM colour number	L4,0	ASTM D1500
Flash Point (Cleveland)	200 °C	ISO 2592
Total base number (TBN)	10,8 mg KOH/g	ASTM D 2896
Sulfate ashes	0,90 %	DIN 51 575

## Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.