

Benefits

1. engineered for latest CVT technology
2. proper friction characteristics even under extreme operating conditions
3. fuel saving potential

Product Description

BIZOL Protect ATF CVT is a high-performance automatic transmission fluid developed specially for the latest generation of Continuously Variable Transmission (CVT) gear boxes. Selected base oils and a well-adjusted additive package protect against foam formation, which is very important for CVT gear boxes. The product has excellent anti-aging and anti-oxidation characteristics. **BIZOL Protect ATF CVT** is suitable for the use in Autotronic gear boxes of the Mercedes A-and-B Class. It is also applicable in many variable automatic transmissions of different manufacturers, among others in Audi Multitronic.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

MB 236.20 | VW G 052 180/G 052 516 | Toyota CVTF FE/CVTF TC |
Mitsubishi CVTF-J1/CVTF-J4/CVTF-4+/SP-III | Nissan NS1/NS2/NS3 |
Suzuki CVTF TC/CVT Green 1&2/NS-2/CVTF 3320 | Hyundai SP-CVT III |
Mini cooper EZL 799 | Honda HMMF/HCF2 |
Subaru High Torque CVTF/ECVT/iCVT/iCVT FG |
Daihatsu Ammix CVT DFE/Ammix CVT Fluid DC/Ammix CVT Fluid DFC |
GM DEX-CVT | Kia SP-CVT III | Mazda JWS 3320 |
Dodge Jeep Chrysler NS-2/Jeep Chrysler Mopar CVT+4

Available Packages

1 L
Art. 27120

Technical Data

Name	Value	Method
------	-------	--------

Viscosity at 40 °C	34,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	7,2 mm ² /s	ASTM D 7042
Viscosity index	183	ASTM D 2270
Density at 15 °C	851 kg/m ³	DIN EN ISO 12 185
Pour Point	<-39 °C	ISO 3016
ASTM colour number	> L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	200 °C	ISO 2592

Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.