

Safety Data Sheet

according to UK REACH Regulation

Bizol Brake Fluid DOT 4

22.01.2018 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bizol Brake Fluid DOT 4

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: BIZOL Germany GmbH Street: Martin-Buber-Str. 12 Place: D-14163 Berlin

Telephone: +49 (30) 804 869-0 Telefax: +49 (30) 804 869-2860

e-mail: support@bizol.de Internet: www.bizol.com

1.4. Emergency telephone Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)

number: In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 -

08454 24 24 24 In Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Irrit. 2; H319 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

dihydro-3-(tetrapropenyl)furan-2,5-dione

Signal word: Warning

Pictograms:



Hazard statements

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

P102 Keep out of reach of children.
P261 Avoid breathing mist/vapours/spray.
P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

DE04

P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

No further relevant information available.

SECTION 3: Composition/information on ingredients



according to UK REACH Regulation

Bizol Brake Fluid DOT 4

22.01.2018 Page 2 of 10

3.2. Mixtures

Revision date:

Chemical characterization

Blend of the following materials with non-hazardous additives.

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation	n)	·	
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]etha	nol		10 - < 25 %
	205-592-6	603-183-00-0	01-2119475107-38	
	Eye Dam. 1; H318	•	•	
111-46-6	2,2' -oxybisethanol			5 - < 10 %
	203-872-2	603-140-00-6	01-2119457857-21	
	Acute Tox. 4, STOT RE 2; H302	H373		
161907-77-3	ethanol, 2-butoxy-, manufacture	< 5 %		
	310-287-7		01-2119475115-41	
	Eye Dam. 1; H318	·		
26544-38-7	dihydro-3-(tetrapropenyl)furan-2,	0,025-<0,25 %		
	247-781-6		01-2119979080-37	
	Eye Irrit. 2, Skin Sens. 1A, Aquat			
128-37-0	2,6-di-tert-butyl-p-cresol			0,025-<0,25 %
	204-881-4		01-2119565113-46	
	Aquatic Acute 1, Aquatic Chronic	1; H400 H410		
67-56-1	methanol			0,025-<0,25 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
143-22-6	205-592-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	10 - < 25 %
	Eye Dam. 1; H	318: >= 30 - 100 Eye Irrit. 2; H319: >= 20 - < 30	
111-46-6	203-872-2	2,2' -oxybisethanol	5 - < 10 %
	dermal: LD50	= 11890 mg/kg; oral: ATE = 500 mg/kg	
26544-38-7	247-781-6	dihydro-3-(tetrapropenyl)furan-2,5-dione	0,025-<0,25 %
	oral: LD50 = 2	900 mg/kg	
128-37-0	204-881-4	2,6-di-tert-butyl-p-cresol	0,025-<0,25 %
	dermal: LD50	= 2500 mg/kg; oral: LD50 = > 6000 mg/kg	
67-56-1	200-659-6	methanol	0,025-<0,25 %
		E = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = l: ATE = 100 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.



Safety Data Sheet

according to UK REACH Regulation

Bizol Brake Fluid DOT 4

22.01.2018 Page 3 of 10

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO2).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO2). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Protective measures: see section 7 + 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Protective measures: see section 7 + 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

No special measures are necessary.

Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities



Safety Data Sheet

according to UK REACH Regulation

Bizol Brake Fluid DOT 4

22.01.2018 Page 4 of 10

Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-46-6	2,2'-Oxydiethanol	23	101		TWA (8 h)	WEL
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
111-46-6	2,2' -oxybisethanol			
Worker DNEL,	long-term	dermal	systemic	106 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	53 mg/kg bw/day
Worker DNEL,	long-term	inhalation	local	60 mg/m³
Consumer DN	EL, long-term	inhalation	local	12 mg/m³
26544-38-7	dihydro-3-(tetrapropenyl)furan-2,5-dione			
Worker DNEL,	long-term	dermal	systemic	0,33 mg/kg bw/day
128-37-0	2,6-di-tert-butyl-p-cresol			
Worker DNEL,	long-term	inhalation	systemic	1,76 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	0,435 mg/m³
Worker DNEL,	long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,25 mg/kg bw/day
67-56-1	methanol			
Worker DNEL,	long-term	dermal	systemic	40 mg/kg bw/day
Worker DNEL,	acute	dermal	systemic	40 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	260 mg/m ³
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	50 mg/m³
Worker DNEL,	acute	inhalation	systemic	260 mg/m³



according to UK REACH Regulation

Bizol Brake Fluid DOT 4

22.01.2018 Page 5 of 10

PNEC values

Revision date:

CAS No	Substance		
Environmenta	al compartment	Value	
111-46-6	2,2' -oxybisethanol		
Freshwater		10 mg/l	
Marine water		1 mg/l	
Freshwater s	ediment	20,9 mg/kg	
Soil		1,53 mg/kg	
26544-38-7	dihydro-3-(tetrapropenyl)furan-2,5-dione		
Marine sedim	ent	0,17 mg/kg	
Freshwater s	ediment	1,7 mg/kg	
Soil		0,2 mg/kg	
Micro-organis	sms in sewage treatment plants (STP)	10 mg/l	
Marine water 0,002 mg/l		0,002 mg/l	
128-37-0	2,6-di-tert-butyl-p-cresol		
Freshwater		0,000199 mg/l	
Freshwater (intermittent releases) 0,00199 r		0,00199 mg/l	
Marine water 0,00002		0,00002 mg/l	
Freshwater sediment 0,0996 mg		0,0996 mg/kg	
Marine sedim	ent	0,00996 mg/kg	
Secondary po	pisoning	8,33 mg/kg	
Soil		0,054 mg/kg	
67-56-1	methanol		
Freshwater		154 mg/l	
Marine water 15,4 mg/l		15,4 mg/l	
Freshwater s	ediment	570,4 mg/l	
Marine sedim	ent	57,04 mg/l	
Soil 23,5 mg/l			

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

- Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept
- Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

blood (B)

Urine (U)

8.2. Exposure controls

Appropriate engineering controls

See section 7. No additional measures necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection.

Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these



Safety Data Sheet

according to UK REACH Regulation

Bizol Brake Fluid DOT 4

22.01.2018 Page 6 of 10

gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (EN 149), e.g. FFA P / FFP3.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: yellowish
Odour: characteristic

Test method

Print date: 29.06.2022

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

> 230 °C

boiling range:

Pour point: not determined

Flash point: > 100 °C EN ISO 2719

Lower explosion limits:

Upper explosion limits:

Auto-ignition temperature:

Decomposition temperature:

PH-Value (at 20 °C):

Viscosity / dynamic:

No information available.

7,0 - 11,5

viscosity / kinematic:

5 - 10 mm²/s

(at 20 °C)

Flow time:

Water solubility:

Completely miscible
Partition coefficient n-octanol/water:

Napour pressure:

Density (at 20 °C):

Relative vapour density:

not determined

1,07 g/cm³

not determined

9.2. Other information

Other safety characteristics

Evaporation rate: not determined

Further InformationNo information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.



Safety Data Sheet

according to UK REACH Regulation

Bizol Brake Fluid DOT 4

22.01.2018 Page 7 of 10

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Exposure route	Dose		Species	Source	Method	
111-46-6	2,2' -oxybisethanol						
	oral	ATE mg/kg	500				
	dermal	LD50 mg/kg	11890	Rabbit			
26544-38-7	dihydro-3-(tetrapropenyl)furan-2,5-dione						
	oral	LD50 mg/kg	2900	Rat	OECD 423		
128-37-0	2,6-di-tert-butyl-p-cresol						
	oral	LD50 mg/kg	> 6000	Rat			
	dermal	LD50 mg/kg	2500	Rabbit	ATE		
67-56-1	methanol						
	oral	ATE mg/kg	100				
	dermal	ATE mg/kg	300				
	inhalation vapour	ATE	3 mg/l				
	inhalation dust/mist	ATE	0,5 mg/l				

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (dihydro-3-(tetrapropenyl)furan-2,5-dione)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

SECTION 12: Ecological information

12.1. Toxicity



according to UK REACH Regulation

Revision date: Bizol Brake Fluid DOT 4

22.01.2018 Page 8 of 10

There are no data available on the mixture itself.

CAS No	Chemical name					
	equatic toxicity Dose [h] [d] Species Source Method					
26544-38-7	dihydro-3-(tetrapropenyl)furan-2,5-dione					
	Acute algae toxicity	ErC50 110 mg/l		Selenastrum capricornutum		

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-46-6	2,2' -oxybisethanol	-1,98 (25°C)
26544-38-7	dihydro-3-(tetrapropenyl)furan-2,5-dione	>=4,39
128-37-0	2,6-di-tert-butyl-p-cresol	5,1

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

List of Wastes Code - residues/unused products

160113

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); brake fluids; hazardous waste

List of Wastes Code - used product

150202

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; absorbents, filter materials, wiping cloths and protective clothing; absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.



according to UK REACH Regulation

Revision date: Bizol Brake Fluid DOT 4

22.01.2018 Page 9 of 10

14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine pollutant: N

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 69, Entry 75

2010/75/EU (VOC): 0 %

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,15.

Abbreviations and acronyms

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen



according to UK REACH Regulation

Revision date: Bizol Brake Fluid DOT 4
22.01.2018 Page 10 of 10

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	On basis of test data
Skin Sens. 1; H317	On basis of test data

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)